



# Rewind® 900 Rib AXA



NO  
WATER  
CONSUMPTION



85% LESS  
ENERGY  
USE



55% LESS  
CARBON  
EMISSIONS

# REWIND®



TECHNICAL DATA	TECHNISCHE DATEN	FICHE TECHNIQUE		
Manufacturing process	Herstellungsart	Méthode de fabrication	DIN 61151	Needle felt
Surface structure	Oberflächenstruktur	Aspect de surface	-	Rib
Pile material	Polmaterial	Composition des fibres	-	100% polypropylene
Pile weight Total weight	Polgewicht Gesamtgewicht	Poids des fibres Poids total	ISO 8543	900 g/m <sup>2</sup>
Roll length	Rollenlänge	Longueur rouleau	-	30 m
Backing	Rückenbeschichtung	Dossier	ISO 2424	None - latex free
Pile height	Polhöhe	Hauteur du velours	ISO 1765	4,5 mm
Total height	Gesamthöhe	Hauteur totale	ISO 1765	9 mm
Permanent anti-static	Permanent antistatisch	Antistatique permanent	ISO 6356	≤ 2kV
Fire Classification	Brennklasse	Comportement au feu	EN 13501-1	Bfl-s1
Thermal resistance	Thermische Beständigkeit	Résistance thermique	ISO 8302	0,1233 m <sup>2</sup> K/W
Impact noise reduction	Trittschallminderung	Réduction du bruit d'impact		24 dB
Resistance to rubbing	Reibechtheit	Résistance au frottement	ISO 105X12	≥ 5
Prodis GUT Certificate	Prodis GUT Zertifikat	Certificat Prodis GUT	-	



## CONTACT

rewind@bintg.com  
www.rewindcarpet.com

A BRAND OF  
**Beaulieu  
International  
Group**



# REWIND® 900 Rib AXA

COLOUR NAME	2M
1098 PEBBLE	✓
2077 CARBON	✓
2158 STORM GREY	✓
2190 ANTHRACITE	✓
2225 STEEL GREY	✓
2266 CHARCOAL	✓
3088 RUBY RED	✓
5100 MIDNIGHT	✓
6099 FOREST	✓
7055 DESERT	✓
7104 DEEP BROWN	✓

